10019475.080902

Attorney Docket: 127FR/50787

CAM No.: 29182.071

symmetry, and wherein the electrodes are formed in such a manner that the gas

discharge forms exclusively in the volume, determined by an alignment of the

openings; and where the plasma channel, generated on the axis of symmetry, is

the source for at least one of the extreme ultraviolet and x-rays; and

means for increasing conversion efficiency.

2. (AMENDED) The device as claimed in claim 1, wherein at least one

of the openings on the side facing away from the space is larger than on the side

facing the space.

3. (AMENDED) The device as claimed in claim 2, wherein the

openings exhibit the shape of a truncated cone.

4. (AMENDED) The device as claimed in claim 1, wherein the anode

opening is designed as a non-continuous depression, and in particular as a blind

hole.

5. (AMENDED) The device as claimed in claim 1, wherein an

auxiliary electrode is provided.

6. (AMENDED) The device as claimed in claim 5, wherein an

auxiliary electrode is provided behind the opening of one of the main electrodes.

2

1341445 TRUCK

Attorney Docket: 127FR/50787

CAM No.: 29182.071

7. (AMENDED) The device as claimed in claim 5, wherein said means

for increasing conversion energy includes an auxiliary electrode, which exhibits

an opening on the axis of symmetry, provided between the main electrodes.

8. (AMENDED) The device as claimed in claim 1, wherein each of

said main electrodes has a plurality of openings.

9. (AMENDED) The device as claimed in claim 8, wherein the

openings in the main electrodes are arranged on a circle, through whose center

runs the axis of symmetry.

10. (AMENDED) The device as claimed in claim 1, wherein each of

said main electrodes has a ring-shaped opening, whereby the center of the ring

lies on the axis of symmetry.

11. (AMENDED) The device as claimed in claim 1, wherein a pulse-

forming network is provided as a power supply.

12. (AMENDED) The device as claimed in claim 1, wherein, in

addition to the gas inlet and outlet opening for the working gas in the electrode

space, there is at least one additional gas inlet or gas outlet opening.

3

10019475 OHOOP

Attorney Docket: 127FR/50787

CAM No.: 29182.071

13. (AMENDED) The device as claimed in claim 1, further comprising

a system of capillaries, for vacuum separation, provided between the gas-filled

space and highly evacuated areas of the device.

14. (AMENDED) The device as claimed in claim 13, wherein the

system of capillaries is a micro channel plate or a Kumakhov lens.

(A copy of the marked-up version of amended claims 1-14 is attached to

this Preliminary Amendment).

IN THE ABSTRACT:

Please substitute the new Abstract of the Disclosure submitted herewith

on a separate page for the original Abstract presently in the application.

REMARKS

Entry of the amendments to the specification, claims and abstract before

examination of the application is respectfully requested. These claims have been

amended to remove multiple dependencies/These claims patentably define over

the art of record.

4